

CROSSBOND[®]
HDF LAMINATE FLOORING

AC4



**AQUA
SHIELD**

***WATER PROOF
WOODEN FLOORING**

V-GROOVE

Locking System by



**Powered
by**  **Välinge**

BOILING *WATER PROOF FLOORING
MADE FOR INDIAN CONDITIONS







ACER TEAK | CB 8614 TX1



CHERRY PINE | CB 8159 TX1



COLUMBIAN WALNUT | CB 8194 TX1



TEVERN OAK LIGHT | CB 8616 TX1



ONTARIO OAK LIGHT | CB 8617 TX1



TECHNICAL SPECIFICATION

PRODUCT FEATURE	TEST STANDARD	AC-4
Abrasion Resistance	EN13329	> 4000
Impact Resistance	EN13329	IC1
Stain Resistance	EN438	Group 5
Cigarette Burns	EN438	Class 5
Light Fastness	EN20105/A02	Class 7
Furniture Legs	EN426	No Damage
Chair Caster (Soft Roll)	EN425	No Damage
Thickness Swelling < 24 hr	ISO 24336	12%
Static Indentation	EN433	0.9 N/MM ²
Flame Resistance	EN13501	CFL-S1
Floor Design Dimensions		1220mm x 194mm x 8mm

* "Water Proof" grade is based on technical standard ISO 24336. Warranties of protection against all types of water exposure, damage, or misuse will be considered as per the thickness swelling criteria mentioned in ISO 24336.

FEATURES



BWP HDF
Flooring



Wax Sealed
Joints



Aluminium
Oxide Overlay



Heaviest Density
(>1000 KG/M³)



Easy To
Install



Various
European Design

CROSSBOND[®]

HDF LAMINATE FLOORING



METRO DECORATIVE PVT. LTD.

Head Office: D-20/1, 2nd Floor, Okhla Industrial Area, Phase-II, New Delhi 110020

Works 1: Village Oogli, Yamuna Nagar Road, Kala Amb, Himachal Pradesh 173030

Works 2: Khasara No. 89, Bankhera Mahua Khera Ganj Road, Village Katiya, Kashipur, Udham Singh Nagar, Uttarakhand 244713

Call: +91-11-41740150 | **Email:** info@crossbondindia.com | **Web:** www.crossbondindia.com

Follow us :      

